

ENVIRONMENTAL PRODUCT DECLARATION

According ISO 14025 and EN 15804

kvadrat shade

ATHOS

COMPANY INFORMATION / DECLARATION OWNER

Manufacturer:	Kvadrat Shade
Production Location:	Kvadrat Shade
Address:	Vonderweg 48 7468DC Enter
E-mail:	contact@kvadratshade.com
Website:	www.kvadratshade.com

EPD INFORMATION

Calculation number:	EPD-NIBE-20201210-15421
Date of issue:	30-12-2020
End of validity:	30-12-2025
Version NIBE's EPD Application:	v2.0
Version database:	v2.95 (2020-12-03)
PCR:	EN15804:2012+A1

VERIFICATION OF THE DECLARATION

CEN standard EN 15804:2012 serves as the core PCR

Independent verification of the declaration. according to EN ISO 14025:2010. Internal External

Verklaring van de toetser, MSc P.F. Stadhouders, 30-12-2020:

"De methodologie en dataverzameling zoals beschreven in dit rapport voldoet aan de eisen van de "Bepalingsmethode Milieuprestatie Gebouwen en GWW-werken" versie 3.0 van november 2019 en de onderliggende normen ISO 14040, ISO 14044 en NEN-EN 15804."

DECLARED UNIT

m2 fabric

m2 of canvass for roller blinds applied to the inside of a window. During its technical life time of 15 years., the canvass meets fire resistance norms EN 13 773, Class 1, BS 5867, part 2, DIN 4102 class B1, NPF P 92 507 class M1, NFPA 701 #1 and IMO. Bar, attachment material and latch are excluded. The production stage (A1-A3), Construction stage (A4-A5), Use stage (B1-B3) and end of life stage (C1-D). In compliance with the Horizontal PCR INSIDE/INSIDE, A4 is considered 1km.

Third party verifier: Msc. P.F. Stadhouders, EcoReview V.O.F.

SCOPE OF DECLARATION

A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	X	MND	MND	MND	MND	X	X	X	X	X

(X = included, MND = module not declared)

PRODUCT DESCRIPTION

The Athos textile is a roller blind fabric. The aim of the roller blind system is to control light and provide acoustic and thermal comfort. The product is made out of Trevira CS polyester that has been treated with several finishes.

The Athos textile is easy to clean, dims out light and ensures privacy. Particularly, the product is suitable for Healthcare establishments, as it can be disinfected and is easy to maintain.

The textile has a lightfastness of 7 and a glare control rating of 4. It has 0% visual light transmission, 4% solar reflection, 96% solar absorption, 29% GTOT/SHGC, and a U-value of 0.94

Furthermore, the textile has passed multiple fire tests; BS 5867 part 2 type B, DIN 4102 B1, EN 13 773 class 1, Chinese GB 50222 B1, IMO FTP Code 2010 Part 7, JIS L 1091 A1-D, NF P 92 507 M1, and NFPA 701.

The textile has a width of 300 cm, weighs 225 g/m², and has an estimated reference service life of 15 years.

DESCRIPTION OF THE MANUFACTURING PROCESS

The raw cloths made of 100% Trevira CS polyester enter the factory ready for production. The raw cloths are treated with dyes and different washing/finishing auxiliaries.

The first step of the process is the washing of the raw cloths in order to degrease the fabric. Washing auxiliaries are diluted with water, with a ratio of 1:10. The textile passes through the bath on rollers, continuously moving through the bath. After the textile is washed it is dyed in the desired color.

After the dyeing process a finish is applied to the textile. For the Athos blind the stiffening and dirt/soil repellent finishing processes are applied. The stiffening will ensure that the textile will hang more straight once assembled and won't crease. The stiffening finish is a thin and clear finish, which is applied to make the textile less flexible and less scratch sensitive. This will prevent the textile for example from cupping or v-shaping once assembled. The dirt/soil repellent finish is a clear coating that is applied to the textile which ensures that the blind is protected from dirt and is easy to clean and therefore can be used in healthcare facilities.

For the most part, the energy use can be attributed to the dyeing process. Furthermore energy is used for the finishing process and the cutting process. The latter of which is a hot process.

The emissions that occur during the production process are related to the burning of gas.

After the textiles are treated they are packaged and transported to the

ENVIRONMENTAL PRODUCT DECLARATION

According ISO 14025 and EN 15804

kvadrat shade

location where the system will be installed.

ENVIRONMENTAL PRODUCT DECLARATION

According ISO 14025 and EN 15804

kvadrat shade

RESULTS

Impact category	Unit	A1	A2	A3	A4	A5	B1	B2	B3	C1	C2	C3	C4	D	Total
ADPE	Kg Sb	4.21E-6	0.00E+0	5.81E-7	1.64E-10	2.53E-7	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.06E-8	1.56E-7	0.00E+0	-5.49E-9	5.22E-6
ADPF	MJ	3.11E+1	0.00E+0	7.19E+0	8.95E-4	1.97E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.13E-1	5.51E-1	0.00E+0	-	3.98E+1
AP	Kg SO ₂ Equiv.	5.40E-3	0.00E+0	1.25E-3	2.49E-7	3.62E-4	0.00E+0	0.00E+0	0.00E+0	0.00E+0	3.14E-5	2.29E-4	0.00E+0	-1.62E-4	7.11E-3
ODP	Kg CFC-11 Equiv.	1.56E-7	0.00E+0	4.53E-8	1.07E-11	1.13E-8	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.35E-9	1.73E-8	0.00E+0	-7.41E-10	2.30E-7
GWP	Kg CO ₂ Equiv.	1.49E+0	0.00E+0	5.00E-1	5.75E-5	1.49E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	7.24E-3	9.28E-1	0.00E+0	-3.41E-2	3.04E+0
EP	Kg PO43-Equiv.	2.39E-3	0.00E+0	3.60E-4	5.02E-8	1.44E-4	0.00E+0	0.00E+0	0.00E+0	0.00E+0	6.32E-6	4.70E-5	0.00E+0	-2.57E-5	2.92E-3
POCP	Kg Ethene Equiv.	5.49E-3	0.00E+0	5.96E-4	3.41E-8	3.09E-4	0.00E+0	0.00E+0	0.00E+0	0.00E+0	4.29E-6	2.21E-5	0.00E+0	-5.17E-5	6.37E-3
Parameter	Unit	A1	A2	A3	A4	A5	B1	B2	B3	C1	C2	C3	C4	D	Total
PERE	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERM	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	MJ	2.70E+0	0.00E+0	8.62E-1	9.41E-6	1.81E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.18E-3	4.30E-2	0.00E+0	-7.91E-1	2.99E+0
PENRE	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PENRM	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PENRT	MJ	3.20E+1	0.00E+0	7.25E+0	9.55E-4	2.03E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.20E-1	5.40E-1	0.00E+0	-	4.07E+1
SM	Kg	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	M3	1.52E-2	0.00E+0	6.02E-3	1.52E-7	1.13E-3	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.92E-5	8.26E-4	0.00E+0	-2.22E-4	2.30E-2
HWD	Kg	5.80E-5	0.00E+0	1.18E-5	5.71E-10	3.60E-6	0.00E+0	0.00E+0	0.00E+0	0.00E+0	7.19E-8	1.60E-6	0.00E+0	-1.46E-6	7.37E-5
NHWD	Kg	1.02E-1	0.00E+0	2.57E-2	5.47E-5	1.48E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	6.88E-3	1.78E-2	0.00E+0	-1.05E-3	1.66E-1
RWD	Kg	4.07E-5	0.00E+0	1.27E-5	6.04E-9	2.94E-6	0.00E+0	0.00E+0	0.00E+0	0.00E+0	7.61E-7	1.85E-6	0.00E+0	-1.71E-7	5.88E-5
CRU	Kg	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	Kg	0.00E+0	0.00E+0	2.25E-3	0.00E+0	4.16E-3	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.25E-2	0.00E+0	0.00E+0	2.89E-2
MER	Kg	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EE	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	3.40E-1	3.40E-1
EET	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.15E-1	2.15E-1
EEE	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.25E-1	1.25E-1
SP	s€	s€ 0,13	s€ 0,00	s€ 0,04	s€ 0,00	s€ 0,01	s€ 0,00	s€ 0,05	s€ 0,00	s€ 0,22					

Impact categories: ADPE=Depletion of abiotic resources-elements | ADPF=abiotic depletion of fossil resources | AP=Acidification of soil and water | ODP=Ozone layer depletion | GWP=Global warming | EP=Eutrophication | POCP=Photochemical oxidants creation

Parameters: PERE=renewable primary energy ex. raw materials | PERM=renewable primary energy used as raw materials | PERT=renewable primary energy total | PENRE=non-renewable primary energy ex. raw materials | PENRM=non-renewable primary energy used as raw materials | PENRT=non-renewable primary energy total | SM=use of secondary material | RSF=use of renewable secondary fuels | NRSF=use of non-renewable secondary fuels | FW=use of net fresh water | HWD=hazardous waste disposed | NHWD=non hazardous waste disposed | RWD=radioactive waste disposed | CRU=Components for re-use | MFR=Materials for recycling | MER=Materials for energy recovery | EE=Exported energy | EET=Exported Energy Thermic | EEE=Exported Energy Electric

ADDITIONAL INFORMATION

Allocation

There is no allocation applied for the environmental profiles / datasets used in this LCA.